

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the Application:

Listing of Claims:

1. (Withdrawn) In a body having a conduit formed of a first passageway having a first longitudinal axis and a second passageway having a second longitudinal axis wherein the first and second longitudinal axes intersect at an angle other than 180 degrees, the improvement characterized by: an enlarged cavity having a center point at the intersection of the first and second longitudinal axes.
2. (Withdrawn) The improvement of claim 1 wherein the enlarged cavity is generally spherically shaped.
3. (Withdrawn) The improvement of claim 2 wherein the diameter of the enlarged cavity is at least twice the cross sectional diameter of one of the first and second passageways.
4. (Withdrawn) The improvement of claim 1 wherein the angle is about 90 degrees.
5. (Withdrawn) The improvement of claim 4 wherein the diameter of the enlarged cavity is at least twice the cross sectional diameter of one of the first and second passageways.
6. (Withdrawn and Currently Amended) A method of manufacturing a body having a conduit with a first passageway having a first longitudinal axis and second passageway having a second longitudinal axis wherein the first and second longitudinal axes intersect at an angle other than 180 degrees, and an enlarged cavity having a center point at the intersection of the first and second longitudinal axes, comprising the steps of: drilling the first passageway into the body

along a first longitudinal axis; drilling the second passageway into the body along the second longitudinal axis until the second longitudinal axis intersects the first longitudinal axis; utilizing ~~electromechanical~~ electrochemical machining to remove material from the walls of the first and second passageways adjacent the intersection of the first and second longitudinal axes until the enlarged cavity with a center point at the intersection is formed.

7. (Withdrawn and Currently Amended) The method of claim 6 wherein the step of utilizing ~~electromechanical~~ electrochemical machining includes removing material evenly in all directions to form a spherical cavity.

8. (Withdrawn) The method of claim 7 further comprising removing material in all directions until the diameter of the cavity is twice the diameter of one of the first and second passageways.

9. (Original) A fuel distribution system for an internal combustion engine comprising: a pump; an injector; a fuel conduit in a body, fluidly connecting the pump to the injector, said fuel conduit being adapted for delivery of fuel at high pressure, having a first passageway with a first longitudinal axis and a second passageway with a second longitudinal axis wherein the first and second longitudinal axes intersect at an angle other than 180 degrees; and an enlarged cavity having a center point at an intersection of the first and second longitudinal axes.

10. (Original) The fuel distribution system of claim 9 wherein the enlarged cavity is generally spherically shaped.

11. (Original) The fuel distribution system of claim 10 wherein the diameter of the enlarged cavity is at least twice the cross sectional diameter of one of the first and second passageways.

12. (Original) The fuel distribution system of claim 11 wherein the angle is about 90

degrees.

13. (Original) The fuel distribution system of claim 9 wherein the diameter of the enlarged cavity is at least twice the cross sectional diameter of one of the first and second passageways.

14. (Original) A unit fuel injector for an internal combustion engine, the unit fuel injector being of the type comprising a pump, an injector, and a body, characterized by: a fuel conduit in the body, fluidly connecting the pump to the injector, said fuel conduit being adapted for delivery of fuel at high pressure, having a first passageway with a first longitudinal axis and a second passageway with a second longitudinal axis wherein the first and second longitudinal axes intersect at an angle other than 180 degrees; and an enlarged cavity having a center point at an intersection of the first and second longitudinal axes.

15. (Original) The unit fuel injector of claim 14 wherein the enlarged cavity is generally spherically shaped.

16. (Original) The unit fuel injector of claim 15 wherein the diameter of the enlarged cavity is at least twice the cross sectional diameter of one of the first and second passageways.

17. (Original) The unit fuel injector of claim 16 wherein the angle is about 90 degrees.

18. (Original) The unit fuel injector of claim 14 wherein the diameter of the enlarged cavity is at least twice the cross sectional diameter of one of the first and second passageways.

19. (Withdrawn) The improvement of claim 1 wherein the diameter of the enlarged cavity is at least twice the cross sectional diameter of one of the first and second passageways.